DRAFT

1.   PURPOSE

Establish a standard process for backing up non-database files on a RISC/6000 AIX or a SUN Solaris server.

2.   SCOPE AND APPLICABILITY

All non-database files running an AIX or Solaris operating system will use these procedures for backup.

3.   PROCEDURE

3.1   Information

The following additional information is pertinent:

3.1.1   Related Documents

    a. Unix Admin Department Naming Standards document.

    b. http://datacenter.sannet.gov

3.1.2   Forms

    a. None

3.1.3   Audience

    a. Unix System Administrators

3.1.4   Assumptions

    a. The User is a Unix System Administrator.

3.1.5   Approvals

    a. ?

3.1.6   Change Management Requirements

    a. ?

3.1.7   Impact

?

Printed copies of this page are for reference only – see online file for controlled copy.

TEP0005A-02

3.2 Working with Backups

3.2.1 On AIX

Step 1:

Use the Tivoli storage manager,

Step 2:

Modify the file

```
/usr/tivoli/tsm/client/ba/bin/dsm.opt
```

3.2.2 On Solaris

Step 1:

Use the Tivoli storage manager,

Step 2:

Modify the file

```
/opt/tivoli/tsm/client/ba/bin
```

3.2.3 On Either Platform

Step 1:

Use the Tivoli storage manager,

Step 2:

Add/modify/delete the **filesystems** after the DOMAIN keyword in a single line delimited by spaces.

> What does this mean? Is there an example?

4. NOTES

4.1 Revision History

Date	Revision	CR No.	Description	Author
12/31/2001	1st Draft		Initial Draft	Steve Almera

Printed copies of this page are for reference only – see online file for controlled copy.

TEP0005A-02

4.2   Diagram

Not Applicable

Printed copies of this page are for reference only – see online file for controlled copy.

TEP0005A-02